

2010-2011 MTTP STREET DIESEL TRUCK RULES

All decisions made by a MTTP official are final.

STREET DIESEL

The Street Diesel (SD) class is designed for full -bodied pulling trucks. With a maximum weight of 8000lbs. the truck also needs to be licensed and insured. Trucks may enter into only one class per event. Pulling order will be determined by random draw.

DRIVERS:

Must be 16 years of age. All drivers must have a valid driver's license. Drivers shall not be under the influence of drugs or alcohol, and must drive their trucks in a safe manner at all times when at the pull.

BALLAST:

Ballast is permitted. Hanging weights are prohibited. Ballast may be added in the bed of the truck.

DRIVELINE:

An OEM transmission and transfer case is mandatory. It must have been optioned in a one-ton or smaller pickup.

DRIVER RESTRAINT SYSTEM:

The OEM restraint system is mandatory and must be worn.

ENGINE:

The engine is limited to a stock appearing, OEM make-specific compression ignition engine.

EXHAUST:

All vehicles must be equipped to direct exhaust upward or downward.

FUEL INJECTION PUMP:

The fuel injection pump is limited to a stock appearing, OEM engine model-specific pump only. Twin CP3's and Hpop's are prohibited.

HITCH:

The hitch must be a "REESE" style hitch. Reinforcements are permitted. Trick hitches are prohibited. The hitches height from the ground may not exceed 26" for 4x4 and 30" for 2x4. Must have a hook point at least 44 inches from the center of the rear axle. The hooking point must have a minimum 3.00 inch by 3.75 inch inside diameter opening for the sled hook.

NITROUS OXIDE:

Nitrous oxide is prohibited. No other oxygen extenders are allowed.

PROPANE:

Propane is prohibited.

REAR SUSPENSION:

Traction bars and devices are permitted. Suspension must maintain a minimum shock travel of 1 inch.

TIRES:

Tires must be DOT street tires. Cut tires are prohibited. A maximum tire diameter of 35 inch.

TRANSMISSIONS:

Transmissions (manual and automatics) must have a transmission blanket meeting SFI 4.1 if running more than 4500 rpm.

TURBOCHARGER:

The turbocharger is limited to a stock, OEM make-specific charger only. Turbochargers from different years in the same make may be interchanged.

WATER INJECTION:

Water injection is prohibited.